





**Auxiliary Speaker** 

## **Description:**

It is suitable for multimedia classrooms, general classrooms, conference rooms, training rooms, specialty stores and other places on demand of reinforcent.

## Features:

- \* Support 1 channel microphone, 1 channel stereo line input, 1 channel stereo line output.
  \* Output overload, overvoltage, short circuit protection.
  \* With mute function, the microphone has priority over the line input.

- \* 1 microphone volume adjustment, 1 line input volume adjustment, 2 treble and bass adjustment.
- \* Built-in HIFI high-fidelity high-end speaker and electronic crossover. Independent amplifier drive for treble and bass .

  \* With 100V broadcast input interface prior to local broadcast.

## **Specifications:**

Model	T-260H
Rated output power	2×25W
Output impedance	4-8Ω
Input sensitivity	AUX IN: 350Mv±20MV/10KΩ; MIC: 5MV±0.5MV
SNR	≥70dB
Frequency response	40Hz~20KHz(≤±3dB)
Line output	1V
Volume adjustment	1 MIC volume, 1 AUX volume
THD	≤1%
Operating temperature	5°C~40°C
Operating humidity	20% to 80% relative humidity, no condensation
Power consumption	≤60W
Supply voltage	~ 220V 50Hz
Dimension (W×H×D) mm	162×240×225
Weight	7.5kg