



In-wall Mounting Box
T-6718



Dimensions: 164 x 78 x 32mm

Surface Mounting Box
T-6719



Dimensions: 169 x 83 x 32mm

Features


- * Double 86-size backbox design, compatible with electrical standard, easy to install.
- * There are two options: single call key (emergency) and double call keys (emergency + business consulting). It can be installed in wall or on wall (with backbox).
- * One key start a call for target terminal, full-duplex communication, achieve simple operation, fast connection.
- * Hand-in-hand connection design, it can be extended with 15 panels at most. The longest distance is 1200 meters with CAT5 cable. 24V DC power supply will be required every 6 panels or every 30 meters distance. With the additional power supply, the distance between intercom panel and controller can be 1200 meters.
- * Built-in non-polarity MIC and amplifying circuit, realizes the high sensitivity field sound collection.
- * Built-in 2W high-fidelity full frequency speaker, making the sound clear and loud.
- * The panel has anti-tamper alarm function to ensure higher safety.
- * High protection grade, adopting alloy material and anti-dismantle screw.

Specifications


Model	T-6716
Electrical Interface	Standard RJ45 input
Support Protocol	RS485
Frequency Response	80Hz~16KHz
Harmonic Distortion	≤ 1%
Signal to Noise Ratio	> 70dB
Assist MIC Input Sensitivity (Unequilibrium)	10mV
Power Output	2W/4Ω
Environment Temperature	-20℃~60℃
Environment Humidity	20%~80% Relative humidity, without condensation
Power Dissipation	≤ 3W
Protection Level	IP55
Size	172 x 86 x 23mm
Weight	0.6Kg

Rear Panel

Front view installation picture



Side view installation picture



Front panel installation diagram

