



### Technical Parameters

Model	TL-JGB0-01
Power Supply	110-240V 50/ 60Hz
Laser Power	3000mw (R: 500mw/638nm+G: 500mw/532nm+B: 2000mw/445nm)
Color	red, green and blue
Motor	N1.8 high precision seismic mirror
Scanning Speed	+/- 30
Shock Mirror	Shock mirror: 30kpps/40kpps high speed fiber optic scanning mirror
Cooling	air cooling
DMX Control Function	DMX control function: 12 channel control, black field function, computer interface, compatible with ILDA standard computer laser show
Software Control	Software control: ILDA's full signal uses electronic switch to convert full-color animated laser, using high-speed seismic scanning speed, pattern with broken pen, strobe, rotation, roll, move, stretch, zoom, fade, speed, color, etc. The effect, with the size adjustment function, built-in 128 beams and animated patterns, can be used for beam animation performance, laser advertising, laser projection
Product Size	24*26*30cm
Air Box Size	42*45*41cm
Product Net Weight	8.5kg
Packing Weight	10kg (carton) 20kg (Flight Case)
Working Environment	indoor/ outdoor plus rain cover
Control Mode	voice control/ automatic DMX512 control/ master-slave synchronization, ILDA interface (can be connected to ISHOW software and imported pangolin, fire Phoenix software)(1 piece)