



Fine Pitch Full Color LED Display

TV-PM125-YX



Descriptions

It has the characteristics of seamless, perfect display, long lifespan, fast frame changing speed, high refresh, good uniformity, wide viewing angle, high gray level and natural color reproduction. It is widely used in command and dispatch, security monitoring, video conferencing, demonstrations and various indoor conference room display areas.

Features

- * It can be used for real-time monitoring and display of the scene, playing various promotional advertisements.
- * The product is seamlessly spliced. And the stitching has no visual black seams.
- * The module of the display is flexible, flat, curved with smooth splicing.
- * DC low voltage power supply, natural heat dissipation without fan and noise.

- * User only needs to maintain a single LED pixel or a single module for failure at low maintenance cost but pretty high speed.
- * Support for picture correction. Adopted Gamma correction technology can achieve point-by-point brightness color correction.
- * Support intelligent light control, which can adjust brightness intelligently, improve picture comfort, and save energy and electricity.
- * Ultra-wide viewing angle display. The display screen has a larger viewing range, and the viewing angle is still clear at any angle.
- * With ultra-high refresh rate, good picture coherence and high picture fluency.
- * The picture is delicate and realistic, and the gray level is still excellent under low brightness.
- * Support ultra HD display. Unique image quality enhancement technology effectively improves image clarity, making high-speed picture smooth without smear.
- * Supports integrated 3D, touch screen and somatosensory games to enhance entertainment and interactivity.

Module Specifications

LED Package Form	SMD1010 black light
Pixel Pitch	1.25mm
Resolution	640000 pixel / m2
Lamp/IC	DSBJ / PWM
Luminous point color combination	1R1G1B
Module resolution	160*120
Module size (mm)	200*150
Panel resolution	320*240
Panel size(mm)	400*300
Panel weight	5Kg/piece
Operating Voltage	DC +4.2V



Main Specifications

Best Viewing Distance	≥3.75m
Horizontal viewing angle	≥160°
Vertical viewing angle	≥160°
Maintenance method	Front maintenance
Graphics card	DVI/HDMI/DP
Video signal	Compatible with PAL/NTSC/SECAM system, support S-Video; VGA; RGB; Composite Video; SDI; DVI; RF; RGBHV; YUV; YC, etc.
Control method	Synchronous control
Drive device	Constant current
Refresh rate	3840Hz
Frame change frequency	≥60Hz
Scanning method	30S
Brightness	650CD/m2 (adjustable)
Gray level	12/14/16bit
Contrast	10000:1
Attenuation rate (after working for 3 years)	≤15%
Brightness adjustment method	Auto / Manual: 1-100%
Computer operating system	WIN98/2000/WIN XP/WIN Vista/WIN7
Mean time between failures	≥10000H
Lifespan	≤100000H
Noise Rate	≤1/100000 and no continuous out of control points
Software	Professional LED display system programming software
Ambient temperature	Storage -35°~+85°, working -10°~+40°
Working voltage (AC)	220V±10%/50Hz or 110V±10%/60Hz
Average power consumption	233W/m2
Maximum power consumption	700W/m2
Installation cabinet specifications	Die-cast aluminum cabinet
Brightness uniformity	≥98%
Protection level	IP5X