



Description

Ideal for prisons, cells, classrooms, offices, various conference rooms, etc. It can achieve audio and video information release, two-way video intercom and other functions.

Features

- * With professional audio and video processing chip and embedded Linux operating system, it is stable and reliable, which satisfies 7*24 hours of uninterrupted and stable operation.
- * Adopt 10.1-inch digital true color display, capacitive touch screen, 1080P HD camera.
- * Support call duty management controller, management center controller, and two-way video intercom.
- * Press the alarm button to cancel the alarm of the video intercom door extension.
- * Support patrol check-in through face recognition, fingerprint recognition, and NFC.
- * Support the display of the door number, the name and number of the person, and the alarm information of the door extension.
- * Support receiving and displaying information content published by the information publishing server.
- * Support external door lights, door magnets, electric locks.
- * Equipped with an installation bottom box (iron) to support embedded installation.
- * Support the docking with third-party business data (prisons, governments, health systems, etc.). And realize the self-service consumption, personnel information inquiry, transformation information inquiry, business interaction of civil police management, online interview and other prison business service query of third-party platforms.

Specifications

Model	TV-6902
Display	10.1-inch digital true color display, capacitive touch screen
Display resolution	1366*768
Internet	Standard RJ45 interface. Support POE power supply
Transmission rate	10/100Mbps
Supporting protocols	TCP/IP, UDP, IGMP, RTP
Audio formats	MP3, WAV
Audio protocols	G.711 a/u, G.722, AAC
Audio sample rates	16KHz~48KHz
Audio modes	16-bit stereo CD sound quality
Built-in speaker impedance power	4Ω, 3W
Audio stream	16Kb ~ 256Kb
Audio port	Built-in MIC
MIC input sensitivity	10mV
THD	<0.5%
SNR	>70dB
Video format	H.264
Video protocols	SIP, RTMP, HTTP
Video stream	128Kb~2Mb
Camera	Built-in, 1080P
Dimensions (L × W × H)	350×40×205mm
Power supply	External DC power supply, POE power supply (with adapter)
Operating Voltage	DC 12V
Operating temperature	-20 ° C ~ +80 ° C
Working humidity	10% to 90% relative humidity
Weight	3kg