







Feature:

- * Color: a 5+1 fixed color panel, two-way stepless rotation, magnet positioning, color index, half-color and other functions.

 * Function: blue sky effect panel, to simulate the effect of white clouds floating.

 * Electric focusing, the clarity can be remotely adjusted in different projection distance.

 * Dimming: 0-100% linear adjustment.

- * Dimming: 0-100% linear adjustment.

 * Strobe: electronic strobe, 0 -25 times/sec (built-in pulse stroboscopic effect).

 * DMX512 port program update, convenient and fast software upgrade via DMX data cable.

 * Over-temperature protection function: built-in NTC temperature control function. When the LED is overheated, the output power will be intelligently reduced.
- * LCD blue screen display. The lamp usage time, software version number and others are displayed.

Specifications:

Model	TL-LT303
Input voltage	AC 110-240V 50/60Hz, 170W
Light source	A 150W White Light LED OSRAM Chip
Average lifespan	50000H
Color temperature	7500K
Beam angle	25°/45°/70°(optional)
Control mode	Comply with the international standard DMX512 signal control protocol, 3-core (5-core optional) DMX512 signal interface; master-slave synchronous control mode, support RDM protocol and program online update function
Operation mode	DMX mode, user program mode, built-in program mode
Channel	5 channels
Fixture material	High-strength die-cast aluminum alloy + copper tube radiator + a waterproof fan to assist heat dissipation
Protection level	Protection IP67
Working temperature	-20°C~45 °C
Fixture size (L×W×H)	230*180*367mm
Package size (L×W×H)	270*250*455mm
Gross weight	10.0kg
Net weight	7.5kg