



# Moving Head Beam Light

## TL-SL155



### Feature:

- \* Dimming: 0-100% linear adjustment.
- \* Color mixing: RGBW stepless color mixing.
- \* Strobe: 1-25 times/sec (conventional strobe, thunder strobe, random strobe, suddenly dark gradually brighter strobe, suddenly bright gradually darker strobe).
- \* Scan range: X-axis 540 degrees, with self-recovery closed-loop system; Y-axis 270 degrees, with self-recovery closed-loop system.
- \* Scanning fine-tuning: X/Y axis 16BIT scanning subdivision for accurate positioning.

### Specifications:

Model	TL-SL155
Input voltage	AC110V-240V 50/60Hz, 300W
Light source	19*15W(4IN1)
Average lifespan	50000H
Beam angle	Adopt quartz light guide, beam angle: 5 -50 degrees
Control mode	DMX512 signal control mode, master-slave control mode (multiple device synchronization) with self-propelled program voice control mode.
Channel	16/24 channels
Fixture material	High temperature resistant plastic + molded alloy material + heat dissipation method / air cooling
Protection level	IP20
Fixture size (L*W*H)	310×200×400mm
Package size (L*W*H)	360×260×460mm
Gross weight	9.8kg
Net weight	8.8kg