



LED Flood Light

TL-SL291



Features

- * Strobe: fast electronic strobe 0-20Hz.
- * Color mixing: RGBW (red, green, blue and white) linear color mixing, 16.7 million colors (0-100% saturation is adjustable), built-in macro function.
- * Electronic dimming: 0-100% independent electronic linear dimming, the camera video is lifelike and flicker-free, the main-spare self-propelled automatic synchronization function, the console normally controls the self-propelled permanent synchronization.
- * Display menu: 0802LCD operation display panel supports invoking various scenes; built-in programs can be directly invoked and executed.
- * Temperature control: temperature intelligent protection function ensures the lifespan of the LED.

Specifications

Model	TL-SL291
Input voltage	AC 110-240V 50/60Hz, 80W
Light source	7×12W LED(4IN1)
Average lifespan	50000H
Lens angle	15°
Fixture connection	Three-pin signal cable IN/OUT, power line IN/OUT
Control method	DMX512, built-in program self-propelled mode, main-spare online mode, support RDM and program online update
Channel	3/4/7 channels
Fixture material	Die-casting aluminum alloy
Protection level	Fireproof V-1, protection IP30
Fixture size (L×W×H)	218×167×279mm
Net weight	4.5kg
Working environment	-20°C~40°C