

Feature:

- * Color: 1 color panel: 6 colors + cooling gobo + white light, half-color effect, variable-speed two-way rainbow effect, step/linear color conversion is optional.

 * Function: 2 water pattern panels, independent rotation, forward and backward stepless rotation; realize the natural water flow effect with the color changing.

 * Dimming: 0-100% linear adjustment.

 * Strobe: electronic strobe, 0-25 times/sec (built-in pulse stroboscopic effect).

- * Spot: the light spot changes with high-speed electric linear zooming.
- * DMX512 port program update, convenient and fast software update via DMX data cable.

 * Over-temperature protection function: built-in NTC temperature control function; when the LED is overheated, the output power will be intelligently reduced.

 * LCD blue screen display. The lamp usage time, software version number and others are displayed.

Specifications:

Model	TL-LT106
Input voltage	AC 110-240V 50/60Hz, 535W
Light source	450W white light LED
Average lifespan	50000H
Color temperature	7000K
Beam angle	25°~50° electric adjustment
Control mode	Comply with the international standard DMX512 signal control protocol, 3-core (5-core optional) DMX512 signal interface;
	master-slave synchronous control mode, support RDM protocol and program online update function
Operation mode	DMX mode, user program mode, built-in program mode
Channel	9 channels
Fixture material	High temperature resistant aluminum alloy + high temperature resistant/UV resistant engineering plastic
	+ copper tube radiator + 1 waterproof fan to assist heat dissipation
Protection level	Protection IP67
Working temperature	-20°C~45 °C
Fixture size (L×W×H)	346×267×541mm