



Description

The wall washer is suitable for panoramic floodlighting of internal and external walls such as government lighting projects, commercial places, stages, conference rooms, display lights, ancient buildings, cultural squares, overpasses, building exterior walls, architectural landmarks, etc. It is also applicable to landscape buildings, outdoor squares and so on.

Features

- * High-power wall washer, stylish and beautiful appearance. Enlarged heat dissipation structure design fully guarantee the stability of LED and long lifespan.
- * The fixture is made of 6063 aluminum alloy mold, the surface is anodized, and the lampshade is made of high-strength semi-toughened glass with impact resistance, friction resistance and excellent rainwater cleaning ability.
- * No glue and waterproof design, protection level IP65.
- * American original LED light source, high luminous flux output, good light color consistency, constant current design; RGB gray level is high, making the dynamic dimming effect softer and colorful.
- * Good electromagnetic compatibility, no electromagnetic interference to the surrounding environment.

Specifications

Model	TL-LH1409
Input voltage/power	DC24V/50Hz/9W
Number of LED bead/light source	San'an 3535/6PCS
Beam angle	10×60°(15, 30, 45, 60° optional)
Color temperature	RGBW(W=5700K)
Control mode	DMX512
Installation method	Fixed
IP rating	IP65
Product size (L×W×H)	300×46×95mm
Packing size (L×W×H)	395×380×280mm
Gross weight	11KG (12PCS/box)
Net weight	0.8KG
Certification	CE/ROHS