

Description:

It is a high-performance digital audio processor highly integrating multiple audio processing technologies, with 4 inputs and 8 outputs. It adopts DSP audio processing technology to provide users with excellent sound quality. It is mainly used in medium and large venues such as stadiums, auditoriums, banquet halls, exhibition halls, and multimedia conferences.

Feature:

- * Each input channel: 4 balanced line inputs, standard XLR interface, balanced connection.
- * Each output channel: 8 balanced line outputs, standard XLR interface, balanced connection.
- * Provide 24bit/48KHz sound quality .

 * Full-featured matrix mixing, flexible and simple signal routing operations, routing path and level size can be finished with one button.
- * Support FIR filter
- * Support automatic memory protection after power failure.

 * Support automatic memory protection after power failure.

 * Support channel gang control function.

 * Support both USB and RJ45 connection methods for PC software control.

- * Equipped with control software, intuitive and graphical interface; support XP/Windows7, 8, 10 and other systems.

Specification:

Model	TS-P480
Input channel	Pre-amplifier, delayer, extender, compressor, 31-band graphic equalizer
Output channel	15-band parametric equalizer, delayer, crossover, FIR filter, high and low pass filter, limiter
Sampling rate	48K
Frequency response	20Hz-20kHz ±0.5dB
THD + noise	<0.002% @1kHz ,4dBu
D/A dynamic range (A-weighted)	120dB
A/D dynamic range (A-weighted)	120dB
Input impedance (balanced)	20ΚΩ
Maximum output impedance (balanced)	100Ω
Channel separation	1kHz, 100dB
Input KCMR	60Hz, 80dB
Maximum output level	+20dBu, balanced
Maximum input level	+20dBu, balanced
Working temperature	0°C-40°C
Power supply	AC110V-220V, 50Hz/60Hz
Power consumption	<40W
Size (width x depth x height)	482×258×45(mm)
Net weight	2.56kg
Gross weight	3.56kg