



Description:

It is a network equipment management platform that integrates prompt configuration, data analysis, central control management, task management, equipment management, permission management, system management and other functions. It is a more humanized and intelligent large-scale cloud management platform to control equipment at any place, any place.

Feature:

- * It adopts the B/S architecture. The equipment of the platform adopts TCP/IP communication. The terminal points can be expanded indefinitely and can be distributed in any network, which can be interconnected without separate wiring.

 * Centralized management of central control equipment, real-time display of equipment status in each zone.

 * Check the occupancy, disabling, and online status of the central control in each area in real time, and initiate task reservation for the online central control.

- * Centralized control of the peripheral equipment. Support equipment failure report.
- * Support the classified management of peripheral equipment and the management of central control area.

 * Data analysis management: you can view the online and offline number of central control equipment according to time, and can view the usage trend of one week/month/year and the summary data of task reservation on the day.
- * User permission management: you can add roles, accounts, and permissions.
- * Event reminder: after information event setting, the platform will automatically send it to the relevant person in charge.

Specification:

Model	TS-9100NW
CPU	Xeon E3-1230v5 (4 cores, 3.4GHz)
RAM	ECC DDR4 8G
Hard disk	2TB Seagate Enterprise Hard Drive
Network card	4 Intel Gigabit Ethernet ports, support port aggregation; 1 remote port
Disk array	Support RAID 0,1,5,10
Video output	1 VGA port
Operating system	Pre-installed Linux Debian 8 64-bit
Other	1 serial port, 6 USB ports (4 USB ports on the rear, 2 USB ports on the front)
Cabinet	1U rack mount
Dimension	660×430×43.5 (mm)
Operating environment	Ambient temperature: 5°C~40°C; relative humidity: ≤75%