





Specification

Model T-205CW Speaker unit 5" woofer x 1, 1.5" tweeter x 1 Rated power 10W Power (100V) 6W/3W/1.5W/0.75W/0.25W Input voltage 70V/100V Impedance 1.67KΩ/3.3KΩ/6.7KΩ/13.3KΩ/4KΩ Speaker impedance 8Ω Frequency response (-10dB) 100Fz-20kHz	
Rated power 10W Power (100V) 6W/3W/1.5W/0.75W/0.25W Input voltage 70V/100V Impedance 1.67KΩ/3.3KΩ/6.7KΩ/13.3KΩ/4KΩ Speaker impedance 8Ω Frequency response (-10dB) 100Hz-20kHz	
Power (100V) 6W/3W/1.5W/0.25W Input voltage 70V/100V Impedance 1.67KΩ/3.3KΩ/6.7KΩ/13.3KΩ/4KΩ Speaker impedance 8Ω Frequency response (-10dB) 100Hz-20kHz	
Input voltage 70V/100V Impedance 1.67KΩ/3.3KΩ/6.7KΩ/13.3KΩ/4KΩ Speaker impedance 8Ω Frequency response (-10dB) 100Hz-20kHz	
Impedance 1.67KΩ/3.3KΩ/6.7KΩ/13.3KΩ/4KΩ Speaker impedance 8Ω Frequency response (-10dB) 100Hz-20kHz	
Speaker impedance 8Ω Frequency response (-10dB) 100Hz-20kHz	
Frequency response (-10dB) 100Hz-20kHz	
······································	
Sensitivity (1m, 1W) 93dB±3dB	
Maximum SPL (rated power) 103dB±3dB	
1KHz coverage angle 120°	
Protection class IP54 (tentative). We can only know after the certification, and the cost is about 1K-2K yuan	
Fixture material UV-resistant ABS front frame and metal back cover	
Installation method Quick screw-in mounting with clip	
Hoisting Reserved nuts for hoisting screws	
Color RAL9016	
Dimension 215*152mm (H×W×D)	
Certification CE certificate	