



Free match
Free to add accessories




Independent research and development
Independent mold development and production



Safe and secure
Built-in constant current drive



Structural waterproof
Integrated structural design



Professional technology
Imported high-efficiency chip



Special protection
Outdoor lightning protection and anti-static



Guangzhou BaoLun Electronics Co., Ltd (Leading Audiovisual and Lighting System Manufacturer)
Factory Add: No. 1, Shilonggang Road, Dalong Street, Shiji Town, Panyu District, Guangzhou City, Guangdong Province
Headquarter Add: Building No.A13-1 Yiku Industrial Park, The Hills, Dongyi Road, Panyu District, Guangzhou China 511492
Website: www.itctech.com.cn info@itc-pa.com.cn

www.itctech.com.cn

LED Flood Light TL-LH3201 >>>



Features



- * Smooth appearance curve, stylish and beautiful appearance. Cavity structure and independent heat dissipation are adopted to fully guarantee the stability and long lifespan of the LED;
- * High-conductivity aluminum radiator, ventilation and convection design, smaller fixture and the larger power. SUS304 stainless steel screw bracket is equipped with a dial, with gear locking function;
- * Glue-free waterproof design, protection level Ip65;
- * The fixture is made of high-strength die-cast aluminum, and the surface is treated with fluorocarbon spraying. The lampshade is made of high-strength tempered glass, which is resistant to impact and friction;
- * Good electromagnetic compatibility and no electromagnetic interference to the surrounding environment.

Product Specification			
Model	TL-LH3201	TL-LH3202	TL-LH3203
Power	15W	10W	10W
Number of LEDs/light sources	CREE/4PCS		
Beam angle	15° (30, 45, 60° optional)		8°
Color temperature	3000K (1900-5700K optional)		
Installation method	Fixed		
IP rating	IP65		
Product size (L×W×H)	85×85×142mm	85×85×92mm	85×85×92mm
Packing size (L×W×H)	670×280×220mm	670×280×175mm	670×280×175mm
Gross weight	12.8KG	10KG	10KG
Net weight	1KG	0.8KG	0.8KG
Certification	CE/ROHS		

info@itc-pa.com.cn

LED Linear Light TL-LH2304 >>>



Features



- * Unique structure, simple and beautiful appearance, waterproof design with full sealant potting, and protection level of Ip65;
- * 6063 aluminum alloy fixture, SUS304 stainless steel screw, multiple installation methods, surface electrostatic spraying paint, strong corrosion resistance, making it suitable for harsh outdoor environments;
- * It has the excellent optical performance, and the external anti-UV PC cover can effectively improve the uniformity of light mixing effects;
- * The integration of monochromatic/RGB/RGBW supports DMX512 control system; concise wiring makes the fixture installation and maintenance more convenient;

Product Specification			
Model	TL-LH2304	TL-LH2305	TL-LH2306
Input voltage/power	DC24V/50Hz/10W	5W	3W
Number of LED lamp	San'an 5050/48PCS	San'an 5050/24PCS	San'an 5050/12PCS
bead/light source			
Beam angle	120°		
Color temperature	RGB		
Control method	DMX512/8 bands	DMX512/4 bands	DMX512/2 bands
Installation method	Fixed (fastener is optional)		
IP level	IP65		
Fixture size (L×W×H)	1000×50×60mm	500×50×60mm	300×50×60mm
Net weight	0.7KG	0.4KG	0.4KG
Certificate	CE/ROHS		

www.itctech.com.cn

LIGHT THE WORLD
ILLUMINATE THE FUTURE

LED LIGHTING

Technology Creates A Better Life

Product Description

LED Wall Washer
LED Street Light
LED Point Light Source
LED Flood Light
LED strip light
LED corrugated light



Related Products <<<



LED POINT LIGHT SOURCE



LED Linear Light



LED WINDOW LIGHT



LED WALL WAHSER



LED UNDERWATER LIGHT



LED UNDERGROUND LIGHT



LED CORRUGATED LIGHT



LED FLOOD LIGHT



LED STREET LIGHT

LED Street Light TL-124 >>>



Features

- * Modular design, simple tools on-site maintenance.
- * IP66 waterproof design, high efficient heat dissipation performance.
- * Intelligent constant current drive technology, breaking the bottleneck of power supply life.
- * Human efficacy light distribution, uniform road lighting.
- * Free serialization, full power solution.

Product Specification		
Product Model	TL-124	
Rated Power	35W	75W
Product Dimension(LxWxH)	355x183x80mm	505x260x95mm
Product Weight	1.3kg	2.95kg
LED Type	SMD3030	
Input Voltage	AC100~270V	
Beam Angel	80°x140°	
Light Source Color Temperature	2200~6500K	
Light Body Material	AL	
Light Body Color	Silver	
Control Mode	Constantly bright	
Environmental Temperature	-20°~50°C	
Luminous Efficiency	>100 lm/W	
Protection Level	IP65	

LED Wall Washer TL-LH1101 >>>



Features

- * Simple appearance design, economical and practical structure;
- * The fixture has high luminous uniformity and brightness;
- * Electronic constant current program design ensures stable quality and long;
- * The light projection angle and position are adjustable, making it always in the best state for the most satisfactory lighting effects.

Product Specification			
Model	TL-LH1101	TL-LH1102	TL-LH1103
Input voltage/power	24W	12W	6W
Number of LED bead/light source	Philips 3030/24PCS	12PCS	6PCS
Beam angle	25°45° (45, 60° optional)		
Color temperature	3000K (1900-5700K optional)		
Installation method	Fixed		
IP rating	IP65		
Product size (L×W×H)	1000×28×77.5mm	500×28×77.5mm	300×28×77.5mm
Packaging size (L×W×H)	1070×340×190mm	570×310×310mm	370×340×370mm
Net weight	1KG	0.6KG	0.4KG
Certification	CE/ROHS		

LED Point Light TL-LH4101 >>>



Features

- * Original appearance design, simple overall appearance, angular, exquisite and beautiful, structural waterproof design, waterproof grade Ip65;
- * High grayscale, high refresh, flicker-free and color design;
- * Uniform and soft luminescence, no dark areas.

Product Specification		
Model	TL-LH4101	TL-LH4102
Input voltage/power	3W	5W
Number of LEDs/light sources	EPISTAR 3535/12PCS	EPISTAR 3535/24PCS
Beam angle	120°	
Color temperature	3000K (1900, 2100, 4000, 5700K optional)	
Installation method	Fixed	
IP rating	IP65	
Size (L×W×H)	122×94×54mm	
Packing size (L×W×H)	535×405×255	
Gross weight	16KG (48PCS/box)	
Net weight	0.3KG	
Certification	CE/ROHS	