







T-8000A T-8000AE

Features:

- * The T-8000A remote paging console is connected with T-8000 through universal industrial standard CAT 5 for zone announcement or communication at a remote and different location from the control center.
- * Each controller provides four RJ45 ports for the remote paging console.

 * The CAT 5 wiring is not only featured of cost-effective, convenient layout, but also integration of RS 485 communication and audio transmission together.

 * Extra DC 24V power supply.

 * Eight zone selector with state indication.

- * Talk and all zone paging swift keys are provided.
- * 2 and 4 tones chimes with selector and off switch.

 * Volume controls are provided for chime and microphone.

 * Full indications includes individual zone, all zone, busy, paging, power, output level to provide a direct visualization.

Specifications:

Model	T-8000A	T-8000AE
MIC	Condenser Microphone	
Frequency Response	50Hz~18KHz (±2dB)	
S/N Ratio	Better than 75dB	
THD	Less than 0.1% at 1KHz,	
Signal Output	0.775V/600Ω	
Mic Input	5 mV/ 6 00 Ω	
Indication	Individual zone, all zone, busy, paging, power, output level indicators	
Protection	DC+24V/2A, Revert fuse protection	
Power Supply	DC 24V	
Power Consumption	5W	
Weight	2.22Kg	0.54Kg
Dimensions	200 x 142.7 x 51.5mm	71 x 143 x 52mm