



Digital Conference Delegate Unit

TS-6200B



Feature:

With new numerical control design.

* With ring-shaped speech indicator light that can show the status of speech. Red light stands for speaking, green light stands for waiting for a speech.

* The special microphone shield design can eliminate the low frequency sound even without using the windproof cotton cover.

* The reelable condenser microphone pole and professional large heart-shaped condenser microphones core make the unit a high sensitivity and intelligibility of the speech.

* The microphone has high and adjustable sensitivity.

* The power of the units is supplied by system host at 24V safe voltage.

* The units are connected by 8-core cables in "T" shape.

* With two groups of 3.5mm stereo sound output socket, can be used for record and earphone connection.

* Built-in HIFI speaker and volume control; with squeal-suppressed function. The built-in HIFI speaker will shut off automatically when the microphone is turned on.

* With discussion / automatic video-tracking function.

Specifications:

| | |
|------------------------|---------------------------------|
| Model | TS-6200B |
| Microphone type | Cardioid electret microphone |
| Frequency response | 80Hz~16KHz |
| SNR | 1KΩ |
| Sensitivity | -34±2dB(0dB=1V/Pa,at 1kHz) |
| Maximum SPL | 100dB(THD>3%) |
| SNR | >80dB |
| Crosstalk | >70dB |
| Dynamic range | >80dB |
| THD | <0.1% |
| MAX power consumption | 2W |
| Headphone load | 8-32Ω |
| Headphone volume | Max 40mW |
| Headphone jack | 3.5mm mono jack |
| Standard | IEC60914 |
| Connector | Comes with 1.8m aviation 8-core |
| Hand-in-hand extension | YES |
| Power supply | Host power supply DC24V |
| Colour | Black |
| Weight | 0.86kg |
| Microphone rod height | 409mm |
| Dimension (LxWxH) | 144×128×62mm |
| Installation method | Desktop |