



# Delegate Unit

## TS-6200D



### Feature:

- \* Unique patented technology; with anti-RF tube to prevent noise and secure a perfect conference environment.
- \* Unique patented appearance, delicate and modernize.
- \* Special microphone head design, even without cotton cover, it can also eliminate the low frequency impact sound.
- \* Professional cardioid capacitor microphone core; with high sensitivity and clear voice; with red and green annular indicator light.
- \* Red indicator light means MIC is on; green indicator light means applying for talking.
- \* With feedback function. When microphone on, built-in speaker will be off.
- \* Built-in speaker and earphone jack, earphone volume is adjustable.
- \* The unit cascade with a professional 8-core aviation plug with a metal fixed nut, which will not loosen or fall off.
- \* The unit comes with a 1.8-meter wire, and the wire is shielded by full-line aluminum foil + waterline, which greatly reduces the interference of strong electromagnetic waves on the wire to avoid noise.
- \* The address code of each unit can be adjusted freely at any time to facilitate construction.
- \* Mic units power supplied by conference controller, 24V DC, safety use.
- \* Hand in hand connection, easy for installation and maintenance.

### Specifications:

Model	TS-6200D
Microphone Type	Cardioid directional electret
Frequency Response	80Hz~16KHz
MIC input Impedance	1K $\Omega$
Sensitivity	-34 $\pm$ 2dB(0dB=1V/Pa,at 1kHz)
Max SPL	100dB(THD>3%)
SNR	>80dB
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Max Consumption	2W
Earphone Load	8-32 $\Omega$
Earphone Volume	Max 40mW
Earphone Jack	3.5mm Mono jack
Standard	IEC60914
Connector	1.8m Aviation 8 core
Power Supply Mode	DC24V
Color	Silver
Weight	0.9kg
Microphone Length	409mm
Dimension(mm)	225(L) $\times$ 131(W) $\times$ 48(H)
Mounting	Desktop