



Ceiling Speaker

TS-208M



Feature

- * Composed of a 8-inch subwoofer and a 1-inch rotatable dome tweeter.
- * With a coaxial 2-way design, the precisely engineered crossover optimizes the response of the vocal section.
- * The tweeter and subwoofer are designed with an inclined angle, which effectively solves the problem of insufficient high-frequency directivity and facilitates on-site debugging for users.
- * Using injection molded PP diaphragm to achieve high-fidelity reproduction of human voice.
- * Frameless magnetic mesh cover design.
- * Built-in adjustable directional tweeter.
- * Suitable for use in indoor places such as high-end conference rooms, hotels and clubs.

Specification

| | |
|-------------------------|--------------------|
| Model | TS-208M |
| Speaker type | Ceiling speaker |
| Rated power | 100W |
| Maximum power | 200W |
| Nominal impedance | 8Ω |
| Frequency range (-10dB) | 55Hz-20kHz |
| Sensitivity (1M/1W) | 93dB±3dB |
| Maximum SPL | 116dB±3dB |
| Coverage angle (-6dB) | 0-120° |
| Subwoofer | 8-inch subwoofer×1 |
| Tweeter | 1-inch tweeter×1 |
| Net weight | 2.8kg |
| Dimension (H×W) | 145×277mm |
| Opening size | 248mm |