



Feature:

- * Rated power: 10KW, output channel number: 3

 * The input voltage of the electric box is AC 380V±15%, and the power frequency is 50Hz. It has protection functions such as overvoltage, surge, short circuit, overcurrent, overload and leakage protection.

 * Built-in lightning arrester, with lightning protection.

 * It contains multi-function card control, with remote control function.

 * Support remote switch power box, remote communication, power monitoring, temperature monitoring, fire monitoring and other operations through LED coreen swart control system software.

- screen smart control system software.

Specifications:

•	
Model	KZX
Manual control	Start button / knob
Automatic control	Control software, multi-function card, remote control
Power capacity (KVA)	10KW
Input wiring	3-phase 4-wire & ground wire
Input voltage	380V
Input frequency	50/60HZ
Output wiring	Single-phase two-wire + ground wire, evenly connected to
Output voltage (V)	the LED screen
Output shunt	AC 220V
Shunt switch capacity (A)	3 channels, single phase AC 220V
Shunt circuit	40A, single phase
breaker installation	Track installation
AC contactor model	CJX2-3210
Lightning protection	CHNT
IP rate	IP44
Dimension(H×W×THK)	500mm*400mm*200mm
Weight	10Kg
Operating temperature	-30°C~70°C