



Moving Head Gobo Light

TL-LT865



Feature

- * Dimming: 0-100% linear dimming.
- * Color wheel: 7 color gels + white light, bidirectional stepless rotation, magnet positioning, color index, half-color and other functions.
- * Gobo wheel: 6 rotating gobo wheels, 6 gobos; gobo positioning, rotation, dithering and other effects.
- * Effect wheel: 1 pattern effect wheel, bidirectional variable speed flow effect.
- * Adjustable focus: DMX linear focusing, ultra-fine and smooth focus adjustment.
- * Prism: Optional triangular prism, rectangular prism, and four-row lens, etc.
- * Atomization: 10%-100%.
- * Strobe: Electronic strobe, 0-25 times/sec (built-in pulse strobe effect).
- * Scanning range: X-axis 540°/4.5 S, Y-axis 270°/2.8 S, with auto return function.
- * Display interface: 2.8-inch LCD widescreen Chinese and English interface, with flip function.
- * Other functions: The input signal has an isolation protection function to ensure stable signal transmission without interference; built-in NTC temperature control function, when the LED is overheated, the output power of the LED will be intelligently reduced; it supports software upgrade through the DMX data line; the lamp usage time, bulb usage time and software version number can be displayed.

Specification

Model	TL-LT865
Input voltage	AC110V~240V, 50/60Hz
Rated power	930W@220V
Light source	1pcs 650W white light LED module
Color temperature	7500K
Service lifespan	20000H
Beam angle	6°-50° linear focusing
Control mode	International standard DMX512 signal, 3-core signal line (five-core optional) DMX512 interface; DMX wireless function optional; self-propelled mode, master-slave mode; support RDM protocol and program online update function
Channel	19/16 channels
Fixture material	High temperature resistant engineering plastic + cast aluminum/wire-drawing aluminum material + copper tube radiator + waterproof fan for heat dissipation
Protection class	Ip66
Fixture size (L×W×H)	457×320×787mm
Package size (L×W×H)	730×670×545mm
Gross weight	47KG
Net weight	42.5KG