



Par Light

TL-SUT204



Feature

- * Strobe: independent electronic strobe 1-25Hz.
- * Color mixing: RGBW (red, green, blue and white) linear color mixing, 16.7 million colors (0-100% saturation adjustment), and built-in macro function.
- * Electronic dimming: 0-100% independent electronic linear dimming, lifelike and flicker-free camera video, the master-slave self-propelled automatic synchronization function, and the console normally controls the self-propelled permanent synchronization.
- * LCD menu: invoke various scenes; built-in programs can be directly invoked and executed.
- * Fixture connection: three-core signal line IN/OUT and power line IN/OUT.
- * Cast aluminum housing, high luminous efficiency, uniform light mixing, and stable performance; equipped with a 1m hand-in-hand power line and signal line of 1 in and 1 out.
- * Voice control sensitivity: 65-130dB.
- * Over-temperature protection function: built-in NTC temperature control function; when the LED is overheated, the output power will be intelligently reduced.

Specification

Model	TL-SUT204
Input voltage	AC 90-250V 50/60Hz, 180W
Light source	18×10W LED (4IN1)

Average lifespan	50000H
Color temperature	3200K~7200K linear adjustment
Beam angle	15°/ 25°/ 35°/45°
Control mode	Multiple voice control, DMX512 (8 channel), built-in self-propelled program, master-slave online mode, support RDM protocol and program online update function
Channel	4/8 channels
Fixture material	Cast aluminum housing
Protection class	Fireproof V-1, protection IP20
Fixture size (L×W×H)	287×215×330mm
Package size (L×W×H)	250×250×360mm
Gross weight	4.1kg
Net weight	3.6kg