



# 200W Moving Head Gobo Light

## TL-SL182



### Feature

- \* Optics: 3 sets of optical lenses with high temperature resistance and strong light transmittance (3-layer coating).
- \* Color wheel: 7 color gels + 1 white light, two-way rainbow effect, adjustable speed, flexible positioning function.
- \* Fixed gobo wheel: 8 fixed gobos + 1 white light, one-way flow, adjustable speed, flexible positioning function.
- \* Rotating gobo wheel: 7 replaceable gobos + white light.
- \* Focus: electronic auto focus.
- \* Prism: rotating triangular prism, forward and reverse rotation, and adjustable speed.
- \* Strobe: with synchronous, asynchronous, random strobe mode, adjustable speed.
- \* Atomization: 1 independent atomization effect, the light spot is soft and natural.
- \* Scanning range: X-axis 630°/2.7 S, Y-axis 270°/1.5 S, accurate scanning positioning.
- \* Display interface: It uses a wide-screen 2.8-inch LCD display interface in Chinese and English; with a rechargeable battery, you can enter the menu to set the address code and perform other settings without powering on; the menu has a hierarchical structure and a friendly graphical interface.
- \* Intelligent heat dissipation: using wind direction drainage and intelligent temperature monitoring technology, built-in NTC temperature control function, when the fault causes the LED to overheat, the output power of the LED will be intelligently reduced.

### Specification

Model	TL-SL182
Input voltage	AC110V-240V 50/60Hz, 280W
LED light source	200W
Average lifespan	50000H
Color temperature	8000K
Beam angle	8-40°
Control mode	DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface (DMX wireless function optional)
Channel	19/14 channels
Fixture material	High temperature resistant plastic + molded alloy material
Protection class	Ip20
Fixture size (L×W×H)	336×240×569mm
Package size (L×W×H)	450×400×555mm
Gross weight	17.5kg
Net weight	15.5kg