



# Two-key Intercom Terminal (Luxurious type)



## T-6703E



Default color is gray, orange color is Optional.



Material: Aluminum Mounting Box



### Description:

It is suitable for both indoor and outdoor environment, with anti-explosion and waterproof features. The user can call to the call center or duty room by press the button.

### Features:

- \* Simple, graceful, use the anti-tamper screw design, high strength panel of 6 mm anti-oxidation alloy, matched with aluminum mounting box to support with both embedded mount installation or surface mount installation.
- \* Embedded PC technology, built-in DSP and high speed industrial chip to ensure start time less than 1 second.
- \* Built-in single network hardware audio decoding module, support TCP/IP, UDP, IGMP (Multicast) protocol, transmit 16-bit audio signal as same as CD quality through network transmission.
- \* Built-in voice intercom call module, supports full-duplex voice intercom and conversation, with high performance DSP sound processing technology, support digital echo elimination and audio compression.
- \* Built-in 3W high-fidelity all frequency speaker to ensure the voice clear and loud, built-in 10W digital rated impedance amplifier to connect with 10W rated impedance speaker.
- \* Built-in high sensitivity microphone, support hands-free calls and customized answer way to achieve large range of sound acquisition and high sound reduction degree.
- \* Built-in monitor function, support management of recording, built-in auxiliary audio IO, can be integrated with surveillance system seamlessly.
- \* Built-in security guards' night patrol and sign in data collection function.
- \* Built-in access state return, access control, fire alarm control, camera tracking and security functions etc.
- \* Support customize call target, one key to making fast call and a key for asking help.
- \* Support multiple call strategy, including call waiting, call forwarding, unanswered reminder.
- \* Support customize the time setting of call forwarding, no one answered, call waiting.
- \* Support for manual and automatic call forwarding, can set the forwarding phone number.
- \* Support for preset shortcut key to broadcast the audio program in the media library, and support for network remote broadcast of the audio program.
- \* Support customize hang up mode, Support for preset shortcut key to broadcast the audio program in the media library, and support for network remote broadcast of the audio program.
- \* Support PSTN phone broadcast and text broadcast.
- \* Support WIFI on demand and on demand of wireless remote control.
- \* Protection grade is IP55, adopt alloy material and anti-dismantle screw.
- \* Support DHCP, compatible routers, switches, Bridges, Modem, Internet, 2G, 3G, 4G, arbitrary, multicast, etc.
- \* Support at least three high security authorization IP configuration scheme, safety level is much higher than the remote configuration scheme.
- \* Authorization operations management functions, support the server configuring and managing the user and password.
- \* Support play function work normally and smoothly during digital audio breakpoint to ensure Broadcast synchronization.
- \* Support prompt function of new configuration intelligent voice reminder.
- \* Support ESD protection. Built-in network isolation anti-thunder processing circuit.
- \* Easy to expand, without being limited by the geographical position. No need for increase management equipment of engine room, simple installation for with network construction design concept.

### Specifications:

Model	T-6703E
Network Interface	Standard RJ45 input
Communication Protocol	TCP/IP, UDP, IGMP (multicast)
Audio Format	MP3
Sampling Rate	8K~48KHz
Transmission Speed	100Mbps
Audio Mode	16-bit CD sound quality
Frequency Response	80Hz~16KHz
T.H.D.	≤1%
S/N Ratio	>70dB
Audio Input Level	350mV, industrial standard press-line connecting terminals
Built-in Speaker Impedance & Power	8Ω/3W
Speaker Output Impedance & Power	4Ω, 10W, industrial standard press-line connecting terminals
Output level	1000mV, industrial standard press-line connecting terminals
Temperature	-20°C~60°C
Humidity	20%~80% Relative humidity, without condensation
Power Consumption	≤20W
Input Power Supply	~190-240V 50/60Hz (power adapter) DC24V/2A
Protection Level	IP55
Dimensions	210 x 105 x 56 mm
Weight	1Kg