



Feature

- * Adopt unique digital U-band transmission technology, pi/4-DQPSK modulation mode, featuring strong anti-interference ability, low bit error rate, and stable transmission performance.
- * Adopt a unique encryption method for audio transmission to protect the content of the meeting.
- * Adopt unique ID code pilot technology to prevent cross-frequency interference
- * One-key frequency scanning to avoid interference; one-key IR frequency binding, easy to operate.
- * With reverberation, treble/alto/bass adjustment.
- * With two balanced outputs and one unbalanced mixing output.
- * The receiver uses a 2.2-inch TFT-LCD screen to display more delicate information.
- * The receiver panel is exquisitely crafted and beautiful.
- * The transmission power is adjustable, and the transmission power can be adjusted as needed.

Specification

Model	T-592U
Frequency range	540MHz-590MHz, 640MHz-690MHz
Receiver sensitivity	-95dBm
Modulation mode	pi/4-DQPSK
THD+N	<0.1%
Maximum output	Balanced output 500mV, unbalanced output 1000mV
SNR	≥105dB (XLR)
Frequency response	20Hz~20KHz ±3dB
Antenna interface	BNC/impedance 50 ohms
Power supply	DC 12V/1A
Working current	≤320mA
Dimension (L×W×H)	443×212×44mm
Weight	2.225kg