



Feature

- * Optics: two sets of high-precision glass optical lens (3-layer coating film).
- * Zoom: any angle optional
- * Strobe: 1-25 times/sec strobe frequency, with synchronous strobe mode, adjustable speed.
- * Display interface: a 3.5-inch widescreen LCD interface in Chinese and English, the hierarchical menu structure and graphical interface are user-friendly.
- * Intelligent heat dissipation: adopt wind direction drainage and intelligent temperature monitoring technology; according to the temperature of different parts of the light, the cooling fans in different parts are automatically started to cool the light components down.
- * Dimming curve: with 4 kinds of dimming curves to adapt to different occasions.
- * Quick replacement of lens modules: The lamp body and optical module are designed with a quick lock device, which is convenient for debugging and replacement of various optical modules.

Specification

Input voltage	AC110V-240V 50/60Hz , 650W
Light source	1pcs 500W white LED
Average lifespan	20000H
Color temperature	7500K
Beam angle	18-43°
Control mode	DMX512 protocol, support RDM protocol and program online update function; (Art-net Ethernet data interface, DMX wireless function optional)
Channel	5 channels
Fixture material	High temperature resistant plastic + molded alloy material
IP rate	Ip20
Fixture size (L×W×H)	340×240×506mm
Package size (L×W×H)	400×375×525mm
Gross weight	18.0kg
Net weight	15.5kg