3W LED Wall Washer TL-LH1806



Description

The wall washer is suitable for panoramic floodlighting of internal and external walls such as government lighting projects, commercial places, stages, conference rooms, display lights, ancient buildings, cultural squares, overpasses, building exterior walls, architectural landmarks, etc. It is also applicable to landscape buildings, outdoor squares and so on.

Features

*Original structural design, internal cavity heat dissipation, simple overall appearance, angular, exquisite and beautiful, structural waterproof design; *Aluminum alloy fixture, double slider fastening bracket, surface outdoor grade electrostatic spraying, strong corrosion resistance, harsh outdoor environment adaptability; *Equipped with imported light source, it has excellent light and color performance, which can effectively improve the light output efficiency of the fixture. Anti-glare shading plate can be used;

*Monochrome/RGB three-in-one/RGBW four-in-one, DMX512 control system. Simple wiring make light installation and maintenance more convenient and faster.

Specifications

Input voltage/power	DC24V/6W
Light source	LUMILEDS/6PCS
Beam angle	10*60°
Color temperature	3000K
Light effect	≥80lm/W
Color rendering index	Ra≥80
Color tolerance	SDCM≤5
Light source life	50000H
Control method	ON/OFF
IK Class	IK08
IP Class	IP65
Shell material	Aluminum + tempered glass
Shell color	Sand gray
Installation method	Bracket screws
Product size (L×W×H)	300*24*38mm
Packaging size (L×W×H)	1030*340*350mm
Net weight/Gross weight	0.35kg/24.1kg(60PCS)