



# LED Wall Washer

## TL-LT621



### Features

- \* Color: RGBW stepless color mixing.
- \* Dimming: 0-100% linear adjustment.
- \* Strobe: electronic strobe, 0-25 times/sec.
- \* DMX512 port program update, convenient and fast software upgrade through DMX data cable.
- \* Over-temperature protection function: built-in NTC temperature control function; when the LED is overheated, the output power of the LED is intelligently reduced.

### Specifications

Model	TL-LT621
Input voltage	AC 110-240V 50/60Hz, 80W
Light source	6*15W (RGBW) 4IN1 LED
Average lifespan	50000H
Color temperature	6500K
Beam angle	20°
Control mode	The control box is needed; comply with the international standard DMX512 signal control protocol, 3-core DMX512 signal interface; master-slave synchronous control mode, support RDM protocol and program online update function
Operation mode	Built-in 3 operation modes (DMX mode, user program mode, built-in program mode)
Channel	4/8/28 channels
Lamp material	High-strength extruded aluminum + die-casting aluminum alloy cover
Protection class	IP65
Working temperature	-20°C~45 °C
Fixture size	562×119×167.5mm (L×W×H)
Packaging size	635×240×190mm (L×W×H)
Gross weight	5.5kg
Net weight	4.6kg