



LED Wall Washer

TL-LH1206



Description

The wall washer is suitable for panoramic floodlighting of internal and external walls such as government lighting projects, commercial places, stages, conference rooms, display lights, ancient buildings, cultural squares, overpasses, building exterior walls, architectural landmarks, etc. It is also applicable to landscape buildings, outdoor squares and so on.

Features

- * Simple appearance design, economical and practical structure;
- * The fixture has high luminous uniformity and brightness;
- * The light projection angle and position are adjustable, making it always in the best state for the most satisfactory lighting effects.
- * Built-in constant current driving circuit, allowing it to maintain efficient illumination. It operates stably over a wide voltage range, improving surge protection capability and avoiding flickering of the lights caused by changes in the external power supply voltage. During the process of connecting the lights in series, it ensures consistent brightness between the first and last light fixtures.

Specifications

| | |
|-------------------------|---------------------------|
| Input voltage/power | DC24V/6W |
| Light source | EPistar/10PCS |
| Beam angle | 30°(45°、60° optional) |
| Color temperature | RGB |
| Light effect | ≥50lm/W |
| Color rendering index | Ra≥70 |
| Color tolerance | SDCM≤5 |
| Light source life | 50000H |
| Control method | DMX512 |
| IK Class | IK08 |
| IP Class | IP65 |
| Shell material | Aluminum + tempered glass |
| Shell color | Sand gray |
| Installation method | Bracket screws |
| Product size (L×W×H) | 300*38*79mm |
| Packaging size (L×W×H) | 370*330*455mm |
| Net weight/Gross weight | 370*330*455mm |
| Remark | Light baffle optional |