



# LED Linear Light

## TL-LH2408



### Description

With the continuous development of urbanization, LED linear lights are used more and more in urban lighting projects. They are very practical and can be freely matched to highlight the outline of buildings, or to make digital screen effects.

### Features

- \* Unique structure, simple and beautiful appearance, waterproof design with full sealant potting, and protection level of IP65;
- \* 6063 aluminum alloy fixture, SUS304 stainless steel screw, multiple installation methods, surface electrostatic spraying paint, strong corrosion resistance, making it suitable for harsh outdoor environments;
- \* The integration of monochromatic/RGB/RGBW supports DMX512 control system; concise wiring makes the fixture installation and maintenance more convenient;
- \* Built-in constant current driving circuit, allowing it to maintain efficient illumination. It operates stably over a wide voltage range, improving surge protection capability and avoiding flickering of the lights caused by changes in the external power supply voltage. During the process of connecting the lights in series, it ensures consistent brightness between the first and last light fixtures.

### Specifications

Input voltage/power	DC24V/6W
Light source	DC24V/6W
Beam angle	120°
Color temperature	RGBW(W=5700K)
Light effect	≥50lm/W
Color rendering index	R <sub>a</sub> ≥70
Color tolerance	SDCM≤5
Light source life	50000H
Control method	DMX512/4 segments
IK Class	IK08
IP Class	IP65
Shell material	Aluminum + tempered glass
Shell color	Sand gray
Installation method	Fixed (optional embedded buckle installation)
Product size (L×W×H)	500*28*40mm
Packaging size (L×W×H)	570*330*395mm
Net weight/Gross weight	0.5kg/14.4kg(24PCS)
Remark	Light baffle optional