



Moving Head Beam Light

TL-SL192



Feature:

- * Color mixing system: CMY+CTO color mixing system stepless color changing.
- * Color wheel: 6 colors + 1 white light.
- * Fixed gobo wheel: 9 gobos + 1 white light, adjustable speed, flexible positioning function.
- * Rotating gobo wheel: 7 replaceable gobos + white light, bidirectional rotation and positioning.
- * Effect gobo wheel: effect wheel/fire effect/water effect supports bidirectional rotation.
- * Pattern cutting system: it can cut triangles, squares, parallelograms, semi-circles; the cutter pattern supports 90° rotation and any positioning function according to the scene.
- * Focusing: linear adjustable focusing/infrared autofocus function.
- * Prism: a quadrangular prism, support bidirectional rotation and positioning.
- * Zoom in: 11× zoom 5-55°.
- * Atomization: two atomizations, support single-layer/double-layer atomization superimposition.
- * Scanning range: X-axis 540~630°/2.7 S, Y-axis 270°/1.5 S, accurate scanning and positioning.
- * Display interface: a wide-screen 2.8-inch LCD interface in Chinese and English, with rechargeable battery, you can enter the menu to set the address code and perform other settings without powering on; the menu is hierarchically structured and has a friendly graphical interface.
- * Intelligent heat dissipation: using wind direction drainage and temperature intelligent monitoring technology, built-in NTC temperature control function, when the LED is overheated, it will intelligently reduce the output power.
- * Aperture function, zoom in and out dynamic effect.

Specifications:

Model	TL- SL192
Input voltage	AC110V-240V 50/60Hz, 800W
Light source	600W
Average lifespan	50000H
Color temperature	6500K
Beam angle	5~53°
Control mode	DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface (DMX wireless function optional)
Channel	39/16 channels
Fixture material	High temperature plastic + molded alloy material
Protection class	IP30
Fixture size (L×W×H)	427×276×765mm
Package size (L×W×H)	515×365×855mm
Gross weight	40.5kg
Net weight	36.5kg