



# Moving Head Light

## TL-SL184



### Feature

- \* Optics: Optical lenses with high temperature resistance and strong light transmission (3-layer coating), three sets of lenses.
- \* Color wheel: 7 color gels + 1 white light, rainbow effect with two-way rotation, adjustable speed, flexible positioning function.
- \* Fixed gobo wheel: 9 fixed gobos + 1 white light, two-way flow, adjustable speed, flexible positioning function.
- \* Rotating gobo wheel: 7 replaceable gobos + white light.
- \* Focusing: electronic auto-focusing
- \* Prism: 3 rotating prisms, support bidirectional rotation, superimposition, and adjustable speed.
- \* Strobe: synchronous, asynchronous, and random stroboscopic mode, and adjustable speed.
- \* Atomization: 1 independent atomization effect, soft and natural light spot.
- \* Scanning range: X-axis 630°/2.7 S, Y-axis 270°/1.5 S, accurate scanning and positioning.
- \* Display interface: A wide-screen 2.8-inch LCD interface in Chinese and English, with rechargeable battery; you can enter the menu to set the address code and perform other settings without powering it on; the menu is hierarchically structured and has a friendly graphical interface.
- \* Intelligent heat dissipation: Using wind direction drainage and temperature intelligent monitoring technology, built-in NTC temperature control function, when it is overheated, the output power of the LED is intelligently reduced.

### Specification

<b>Input voltage</b>	AC110V-240V 50/60Hz , 430W
<b>LED light source</b>	300W
<b>Average lifespan</b>	50000H
<b>Color temperature</b>	6500K
<b>Beam angle</b>	8-40°
<b>Control mode</b>	DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface (DMX wireless function optional)
<b>Channel</b>	19/14 CH
<b>Fixture material</b>	High temperature resistant plastic + molded alloy material
<b>Protection class</b>	Ip20
<b>Fixture size (L×W×H)</b>	336×240×569mm
<b>Package size (L×W×H)</b>	450×400×555mm
<b>Gross weight</b>	17.5kg
<b>Net weight</b>	15.5kg