

## Feature:

- \* Color wheel: 7 color gels + white light, two-way stepless rotation, magnet positioning, color index, half-color and other functions.

  \* Gobo wheel: 6 rotatable gobo wheels, 6 gobos; support pattern positioning, rotation, dithering, etc.

  \* Function: a dynamic effect wheel, two-way stepless rotation.

  \* Prism: triangular prism, quadrilateral prism, four row lens and so on.

  \* Atomization, 10%-100%.

  \* Light spot changing, and high-speed electric linear focusing.

  \* Dimming: 0-100% linear adjustment.

  \* DMX 12 port program undate, convenient and fast software upgrade through DMX data cable.

- \* DMX512 port program update, convenient and fast software upgrade through DMX data cable.

  \* Over-temperature protection function: built-in NTC temperature control function. When the LED is overheated, the output power will be intelligently reduced.
- \* LCD blue screen display, including the lamp usage time, software version number, etc.

## **Specifications:**

| Model                | TL-LT205  |
|----------------------|---|
| Input voltage        | AC 110-240V 50/60Hz, 600W   |
| Light source         | A 550W White Light LED OSRAM chip   |
| Average lifespan     | 50000H  |
| Color temperature    | 7500K   |
| Beam angle           | 5°- 50°linear focusing  |
| Control mode         | Comply with the international standard DMX512 signal control protocol, 3-core (5-core optional) DMX512 signal interface; master-slave synchronous control mode, support RDM protocol and program online update function |
| Operation mode       | DMX mode, user program mode, built-in program mode  |
| Channel              | 15 channels   |
| Fixture material     | High-resistant aluminum alloy + high temperature resistant/UV resistant engineering plastic + copper tube radiator + a waterproof fan to assist heat dissipation  |
| Protection class     | IP67  |
| Working temperature  | -20°C~45°C  |
| Fixture size (L×W×H) | 541×267×346mm   |
| Net weight           | 26.5kg  |