



Feature:

- * DMX512/1990 standard, a maximum of 256 DMX control channels, and one photoelectric isolation signal output.
- * Control a maximum of 16 computer lights or 64 dimming channels.

- * Automatically generate the lamp library. * Backlight LCD display, Chinese and English language switching. * The built-in graph trajectory generator has 35 built-in graphs, which are convenient for users to control graphics trajectory of the computer lights, including circle, spiral, rainbow, chasing and other effects.
- * Graphic parameters (such as amplitude, speed, interval, wave and direction) can be set independently, making it more convenient to design the desired shapes and scenes.
- * 80 playback scenarios can be stored for multi-step scenario and single-step scenario. Each multi-step scenario can store up to 100 scenarios.
 * 16 playback scenarios can be output and run simultaneously.
- * Equipped with 16 centralized fader; support button control and fader control.
- * Data can be kept in memory if shutdown or sudden power outage happens.
- * Support console data backup and re-importing data to console via a U disk. Data in the console of the same model can be shared.
- * Support remote software upgrade. You can add new functions anytime and anywhere. * You can control the attributes of the computer light by preset fader, which is more convenient and fast.

* Support immediate fade-out.

Specifications:

Model	TL-SL702
Input voltage	AC 110-240V 50/60Hz
Fixture size (L×W×H)	480×220×75mm
Package size (L×W×H)	540×260×128mm
Gross weight	4.6kg
Net weight	4kg