

Feature

- * Color mixing system: CTO stepless linear change.
- * Color wheel: 5 colors, 1 white light.
- * Aperture function: White light linear scaling function.
- * Focus: Linear adjustment manual focus.
- * Zoom in: Manual zoom.
- * Display interface: adopts 1.5-inch LCD screen display interface.
- * Intelligent heat dissipation: Using wind direction drainage and intelligent temperature monitoring technology, built-in NTC temperature $control\ function,\ when\ the\ fault\ causes\ the\ LED\ to\ overheat,\ the\ output\ power\ of\ the\ LED\ will\ be\ intelligently\ reduced.$

Specification

| Input voltage AC110V-240V 50/60Hz,630W LED light source 600W LED Color temperature 6200K Beam angle 9~14° Control mode DMX512 protocol, support RDM protocol and program online update function Channel 6 channels Fixture material High temperature resistant plastic + molded alloy material Protection class Ip30 灯具尺寸(L×W×H) 1121×402×425mm 包装尺寸(L×W×H) 1190×470×400mm Fixture size (L×W×H) 29.5kg Package size (L×W×H) 27.9kg | | |
|---|----------------------|--|
| LED light source50000HColor temperature6200KBeam angle9~14°Control modeDMX512 protocol, support RDM protocol and program online update functionChannel6 channelsFixture materialHigh temperature resistant plastic + molded alloy materialProtection classIp30灯具尺寸(L×W×H)1121×402×425mm包装尺寸(L×W×H)1190×470×400mmFixture size (L×W×H)29.5kg | Input voltage | AC110V-240V 50/60Hz , 630W |
| Color temperature 6200K Beam angle 9~14° Control mode DMX512 protocol, support RDM protocol and program online update function Channel 6 channels Fixture material High temperature resistant plastic + molded alloy material Protection class Ip30 灯具尺寸(L×W×H) 1121×402×425mm 包装尺寸(L×W×H) 1190×470×400mm Fixture size (L×W×H) 29.5kg | LED light source | 600W LED |
| Beam angle 9~14° Control mode DMX512 protocol, support RDM protocol and program online update function Channel 6 channels Fixture material High temperature resistant plastic + molded alloy material Protection class Ip30 灯具尺寸(L×W×H) 1121×402×425mm 包装尺寸(L×W×H) 1190×470×400mm Fixture size (L×W×H) 29.5kg | LED light source | 50000H |
| Control modeDMX512 protocol, support RDM protocol and program online update functionChannel6 channelsFixture materialHigh temperature resistant plastic + molded alloy materialProtection classIp30灯具尺寸 (L×W×H)1121×402×425mm包装尺寸 (L×W×H)1190×470×400mmFixture size (L×W×H)29.5kg | Color temperature | 6200K |
| Channel6 channelsFixture materialHigh temperature resistant plastic + molded alloy materialProtection classIp30灯具尺寸 (L×W×H)1121×402×425mm包装尺寸 (L×W×H)1190×470×400mmFixture size (L×W×H)29.5kg | Beam angle | 9~14° |
| Fixture material High temperature resistant plastic + molded alloy material Protection class Ip30 灯具尺寸(L×W×H) 1121×402×425mm 包装尺寸(L×W×H) 1190×470×400mm Fixture size (L×W×H) 29.5kg | Control mode | DMX512 protocol, support RDM protocol and program online update function |
| Protection class lp30 灯具尺寸 (L×W×H) 1121×402×425mm 包装尺寸 (L×W×H) 1190×470×400mm Fixture size (L×W×H) 29.5kg | Channel | 6 channels |
| 灯具尺寸(L×W×H) 1121×402×425mm 包装尺寸(L×W×H) 1190×470×400mm Fixture size (L×W×H) 29.5kg | Fixture material | High temperature resistant plastic + molded alloy material |
| 包装尺寸(L×W×H) 1190×470×400mm Fixture size (L×W×H) 29.5kg | Protection class | Ip30 |
| Fixture size (L×W×H) 29.5kg | 灯具尺寸(L×W×H) | 1121×402×425mm |
| | 包装尺寸(L×W×H) | 1190×470×400mm |
| Package size (L×W×H) 27.9kg | Fixture size (L×W×H) | 29.5kg |
| | Package size (L×W×H) | 27.9kg |