



Description

Ideal for conference halls, banquet halls, multi-function halls, high-end clubs, etc.

Feature

- * Made of 15mm birch CNC cutting technology. The internal reinforcement ribs are fixed at multiple points to increase the stability of the cabinet. The surface is sprayed with water-based paint to make it strong and wear-resistant.
- * Integrated into a hard and thick rigid protective grille, and covered with high sound transmittance acoustic mesh to protect the speaker and increase its service life.
- * Adopting a front-oriented two-way design, the sound pressure is abundant and the timbre is comfortable. It optimizes the power response and the mid-frequency performance of the vocal part. The treble is clear and the bass is soft and elastic.
- * Adopt 10" neodymium magnetic mid woofer and a 44mm compression neodymium magnetic tweeter.
- * Multiple screw pendant holes, a 35 mm diameter pole socket, multiple installation methods.

Specification

Impedance	8Ω
Frequency response	45Hz-20kHz
Rated power	300W
Peak power	1200W
Sensitivity	98dB/W/m
Max SPL (rated/peak)	123dB/129dB
Coverage angle	(H)90°(V)70°
Tweeter	44mm compression tweeter × 1
Woofer	10" bass × 1
Dimension (H×W×D) mm	510×315×290
Weight	14.9kg