



Description

The wall washer is suitable for panoramic floodlighting of internal and external walls such as government lighting projects, commercial places, stages, conference rooms, display lights, ancient buildings, cultural squares, overpasses, building exterior walls, architectural landmarks, etc. It is also applicable to landscape buildings, outdoor squares and so on.

Feature

- *Original structural design, internal cavity heat dissipation, simple overall appearance, angular, exquisite and beautiful, structural waterproof design;
- *Aluminum alloy fixture, double slider fastening bracket, surface outdoor grade electrostatic spraying, strong corrosion resistance, harsh outdoor environment adaptability ;
- *Equipped with imported light source, it has excellent light and color performance, which can effectively improve the light output efficiency of the fixture.
- *Simple wiring make light installation and maintenance more convenient and faster.
- *Built-in constant current driving circuit, allowing it to maintain efficient illumination. It operates stably over a wide voltage range, improving surge protection capability and avoiding flickering of the lights caused by changes in the external power supply voltage. During the process of connecting the lights in series, it ensures consistent brightness between the first and last light fixtures.



Specification

Input voltage/power	AC110V-240V 50/60Hz /36W
Light source	LUMILEDS/30PCS
Beam angle	10*60° (15°、30°、45°、60°optional)
Color temperature	3000K (1900K、2100K、4000K、5700K optional)
Light effect	≥80lm/W
Color rendering index	Ra≥80
Color tolerance	SDCM≤5
Light source life	50000H
Control method	ON/OFF
IK Class	Ik08
IP Class	Ip67
Shell material	Aluminum + tempered glass
Shell color	Sand gray
Installation method	Bracket screws
Product size (L×W×H)	500*80*148mm
Packaging size (L×W×H)	570*390*155mm
Net weight/Gross weight	Net weight/Gross weight 2.35KG/5.8KG (2PCS)