



260W Moving Head Beam Light

TL-SL101C



Feature:

- * Optics: two sets of high-precision glass optical lens (3-layer coating film), two sets of lenses.
- * Color wheel: 14 color gels + 1 white light, two-way rainbow effect, adjustable speed, and flexible positioning function.
- * Fixed gobo wheel: 16 fixed gobos + 1 white light, one-way flow, adjustable speed, and flexible positioning function.
- * Prism: rotating hexadecagon prism + 6 row lens, support two-way rotation, superimposition, and adjustable speed.
- * Strobe: double-chip strobe 0.5-13 times/sec, support synchronous, asynchronous, random stroboscopic mode, and adjustable speed.
- * Atomization: 1 independent atomization effect with soft and natural light spot.
- * Scan range: X-axis 630°/2.7 S, Y-axis 270°/1.5 S, accurate scanning and positioning.
- * Display interface: a 2.8-inch widescreen LCD interface in Chinese and English that supports a rechargeable battery. You can enter the menu for address code setting and other settings without power on; the hierarchical menu structure and graphical interface are user-friendly; it supports normal operations of the touch screen, including click, double click, and slide, etc.
- * Intelligent heat dissipation: adopt wind direction drainage and intelligent temperature monitoring technology; according to the temperature of different parts of the light, the cooling fans in different parts are automatically started to cool the light components down.
- * Special functions: Gyroscope (optional): Gyroscope function is turned on, Y-axis automatic compensation calibration, autofocus: 3-25.5 meters autofocus.

Specification:

Model	TL-SL101
Input voltage	AC110V-240V 50/60Hz, 350W
Ballast	Electronic ballast
Light source	260W light bulb
Average lifespan	2000H
Color temperature	8000K
Beam angle	2.5°
Control mode	DMX512 protocol, support RDM protocol and program online update function; (Art-net Ethernet data interface and DMX wireless function optional)
Channel	14/17 channel
Fixture material	High temperature resistant plastic + molded alloy material
Protection class	IP20
Fixture size (L×W×H)	340×240×506mm
Package size (L×W×H)	400×375×525mm
Gross weight	17.5kg
Net weight	15.0kg