



Description

The Visual intercom controller is the control center of the video intercom system. It adopts an embedded platform operating system and uses a server-level Linux system as the core operating platform, which protects the system from virus interference and damage and greatly improves the system's operating stability .

Specification

Processor	Standard configuration: Zhaoxin KX-U6780A (2.7GHz, eight cores and eight threads) TDP 70W
Harddisk	Support hot-swap, support up to 8 hard disks, standard 8 hard disk boxes, compatible with 3.5 and 2.5-inch hard disks, support Raid 0 1 5 10, standard 1*3.5-inch 1T enterprise-level hard disk
Memory	Standard 8GB DDR4 2666 desktop memory
I/O Interface	1*COM (RS232) port ; 2*RJ45 Gigabit Ethernet port ; 4 *USB2.0 port ; 4*USB3.0 port ; 1*VGA port ; 1*HDMI port ; 1*DVI port ; 1*PS/2 ; 1*LINE IN; 1*LINE OUT; 1*MIC IN
Audio formats supported	AAC , WAV , MP3 , APE , OGG , M4A
Supported image formats	BMP , JPG , JPEG , PNG , TIFF
Video support formats	MP4 , SWF , RM , AVI , MOV , FLV , 3GP , RMVB
Audio encoding format	AAC
Video encoding format	H264
Network protocol	HTTP, RTMP, RTSP, TCP, UDP, ICMP, ONVIF
Network speed	10/100/1000Mbps
Power supply	550W 1+1 redundant power supply (input: 100-240 V AC)
Operating voltage	AC 100-240V
Ambient temperature	10°C ~ 35°C (working state) -40°C ~ 55°C (non-working state)
Relative humidity	10% ~ 80% (working state) 0% ~ 95% (non-working state) No condensation
Dimensions (L x W x H)	490 × 435 × 90mm
Net weight	7.4kg
Gross Weight	9kg