



Description:

The professional LED display control equipment supports powerful video signal receiving, splicing and processing capabilities, and can receive a maximum of 1920*1200 HD digital signal. Designed with HDMI, DVI and other digital interfaces, it supports seamless switching between multiple signals. A single unit can support LED displays with a maximum of 4096 horizontal pixels or a maximum of 2560 vertical pixels, which enable it to perfectly apply to rental LED display and small LED displays.

Features:

- *Support 2.60million custom pixel output in output mode, support a maximum of 4096 horizontal pixels or a maximum of 2560 vertical pixels.
- *Support the maximum input resolution 1920*1200@60Hz, support arbitrary setting of resolution.
- *Support 4 Gigabit Ethernet port output, support single or dual redundant backup.
- *Support arbitrary switching, cropping, splicing, and scaling of video signals.
- *Support screen shift.
- *Support independent audio input.
- *Support HDCP high-bandwidth digital content protection technology.
- *Support brightness and color temperature adjustment.
- Support low brightness and high gray, effectively keep the complete and perfect display of gray scales in low brightness.

Specifications:

Input interface	
HDMI*1	HDMI 1.4, support 1920*1200@60Hz, support HDCP
DVI*2	VESA standard, support 1920*1200@60Hz, support HDCP
AUDIO*1	Audio input, used with multi-function card (optional)
Output interface	
Port*4	RJ45, 4 Gigabit Ethernet port output, 4 Ethernet ports can be spliced up, down, left and right arbitrarily
Control interface	
USB_OUT*1	USB output, used for cascading between devices
USB_IN*1	USB input, connected to PC for parameter debugging
Power supply	100~240VAC
Dimension	Standard 1U cabinet
Weight	2.0kg
Rated power	8W