



## Visitation extension TH-3110TSU

### Embedded software: Visitation extension Android terminal software V2.097



## Description

The visitation extension is installed in the visitation room and supports initiating visitation applications and entering the visitation screen to communicate visually with the patient.

## Feature

- \* Equipped with a quad-core processor, providing powerful computing power and processing speed to ensure smooth user experience and efficient task processing.
- \* Precise multi-touch function allows users to operate and control by touching the screen, providing a more intuitive and convenient interaction method.
- \* Equipped with a 10.1-inch high-resolution display, presenting delicate images and clear text, providing a richer visual experience and a more comfortable reading environment.
- \* With great brightness performance, it can be clearly seen even in bright environments, enhancing the applicability and usability of the product.
- \* Support wired network connection, providing stable and high-speed network connection, suitable for scenarios that require large-traffic data transmission or require network stability.
- \* Equipped with a serial port 8P-2.0mm socket for convenient connection and communication.
- \* Equipped with a 5-megapixel camera, capable of shooting high-definition images and videos.
- \* Built-in dual microphones can realize two-channel recording and audio collection, improving audio quality.
- \* Support Chinese and English multi-language OSD operation interface, users can choose the appropriate language for operation according to their own needs.
- \* Support server offline reminder and terminal offline reminder;
- \* When family members initiate a visit, they only need to check the patient's ward number, bed number and name. Once the identity verification is passed, the visit can begin;
- \* The remaining time of the visit is displayed on the visit screen, and the volume and brightness can be adjusted according to needs. Family members can apply to increase the visit time and support early ending of the visit;
- \* Support viewing local machine information, setting volume and brightness.



## Visitation extension TH-3110TSU

### Embedded software: Visitation extension Android terminal software V2.097

#### Specification

|                             |  |
|-----------------------------|--|
| CPU                         | Quad-core, main frequency 2.0GHZ   |
| Memory                      | 2GB  |
| Hard disk                   | 16GB   |
| Operating system            | Android 11   |
| Touchscreen                 | 10-point capacitive touch  |
| LCD screen                  | 10.1 inches  |
| Resolution                  | 1280×800   |
| Viewing angle               | 85/85/85/85°   |
| Display mode                | Always black   |
| Contrast                    | 800  |
| Brightness                  | 250cdm2  |
| Dscreen ratio               | 16:10  |
| WiFi                        | 802.11b/g/n/ac,2.4G/5G   |
| Bluetooth                   | Bluetooth 5.0  |
| Ethernet                    | 100Mbps/1000Mbps   |
| Type-c                      | Only support USBOTG function   |
| Network port                | RJ45 Ethernet interface  |
| Voice control port          | 6P-2.0mm socket (connects to external handheld microphone)                         |
| USB                         | USBHost2.0   |
| Serial port                 | 8P-2.0mm seat (TTL level)  |
| Headphone holder            | 3.5mm stereo headphone output with microphone input                                |
| Video format                | MPEG-1, MPEG-2, MPEG-4, H.265, H.264, VC-1, VP8, VP9, etc., support up to 4K video |
| Audio format                | MP3/WMA/AACetc   |
| Image Format                | Jpeg/png   |
| Wall hanging                | 100×100mm standard wall mounting VESA hole   |
| Speaker                     | 2×3W   |
| Camera                      | Normal angle 5 million pixels  |
| Built-in microphone         | Standard dual microphones  |
| Operating temperature range | 0~40℃  |
| Power supply                | DC12V/1.5A+POE power supply  |
| Machine rated power         | ≤18W   |
| Size                        | 266.11×28.9×184.89mm   |
| Weight                      | 0.81kg   |