



# Professional Column Speaker

## TS-1203K



### Description

Applicable to: language sound reinforcement systems in small and medium-sized video conference rooms, digital courts, conference centers, lecture halls, lecture halls, etc., background music systems in various architectural spaces such as churches, museums, transportation hubs, square public areas , etc.

### Features

- \*It uses 12 3-inch woofers and 1 1.4-inch tweeter .
- \*The shell is made of aluminum alloy reinforced box, with a newly designed matte black color. It has a beautiful and practical appearance and is suitable for sound reinforcement in various building spaces .
- \*High-performance array sound columns can provide good sound reinforcement in some complex environments with high natural reverberation coefficients, echoes, and architectural obstacles in the language and music listening space .
- \*Sturdy, durable, hard and thick rigid mesh protection, one-piece stamping and covered with high-sound-transmittance acoustic mesh cotton, can prevent dust or liquid from entering and affecting the sound quality, protect the speaker and increase its service life .
- \*It is particularly suitable for use in medium and long distance sound reinforcement environments and in various indoor architectural spaces .
- \*With adjustable angle mounting bracket or narrow wall mounting bracket.

### Specification

Type	Conference full-range column speaker
Rated power	400W
Peak power	1600W
Nominal impedance	4Ω
Frequency range (-10dB)	80HZ-20KHZ
Sensitivity (±3dB)	94dB (1m/1W)
Maximum sound pressure level (rated/peak)	120dB/126dB
Speaker unit	3" full range × 12
Coverage angle (-6dB)	160° (H) 20° (V)
Input interface	1 × NL4 1 × Phoenix plug
Product size (W×D×H)	95×118×1140mm
Net weight	9.2 kg