



Features

- *Dimming: 0-100% electronic linear dimming, jitter-free smooth dimming technology.
- *Strobe: 0-25 times/second electronic strobe, speed adjustable, built-in random strobe or pulse strobe.
- *Focus: Manual focus.
- *Graphic cutting disc: 4 independent manual cutting discs, cutting at any angle to adjust the spot shape.
- *Display interface: LCD display; equipped with 4 mechanical buttons; supports inverted display.

Specification

Input voltage	AC 110-240V, 50/60Hz
Rated power	300W
Power factor	PF≥0.98
Light source	300W White LED COB
Average lifespan of light source	50000H
Color temperature	4200K
Color tolerance	SDCM≤3
Luminous flux	5698lm
Color rendering index	Ra≥95
Beam angle	19°
Control method	DMX512 protocol, RDM protocol, built-in master-slave mode, manual control mode
Channel mode	Standard mode 2CH
Housing material	die-cast aluminum
Power interface	1 power input interface, 1 power output interface
Signal interface	1 DMX512 input interface, 1 DMX512 output interface
Working environment temperature	-20°C ~ 45°C
Protection level	Ip65
Product dimensions (L×W×H)	680×340×237mm
Packing dimensions (L×W×H)	750×530×745mm (carton)
Gross weight of packaging	13.6kg(1pcs)
Product net weight	11.9kg