



Description

The secondary triage screen is placed at the entrance of the clinic or the examination window. It is suitable for medical scenarios, displays the information of the attending doctors and the patient queue information, and supports number calling playback

Features

- *Supports displaying the information of the doctor currently sitting in the clinic, including the doctor's photo, name, title, and introduction.
- *Supports display of patient information, including current patient information, next patient information, and patient waiting in line information.
- *It supports displaying promotional slogans at the bottom of the screen, and the slogan content can be modified through the background software.
- *Supports background remote upgrade.
- *Supports privacy protection of patient names, and displays patient names with an asterisk (*), such as Zhang* and Huang*yi.
- *Supports call number prompts, patients whose numbers are called will receive special prompts, and supports voice broadcast.
- *The device's calling voice volume can be adjusted in the background, and the display interface can be remotely screenshotted.
- *Support setting any time period for scheduled power on and off.
- *Supports log viewing function.
- *Supports replacement of display templates, and can customize template styles according to the on-site environment.



Specification

Screen size	21.5 inches
Resolution	1920 * 1080
Screen ratio	16:9
Brightness	250 cd/ m²
Contrast	1200:1
Viewing angle	178°
Backlight life	50000Hrs
Glass hardness	Explosion-proof tempered glass, Mohs 7 hardness
CPU	Quad-core, main frequency 1.8GHz
Running memory	2 GB DDR4
System memory	32GB
Android system version	Android 11
Built-in speakers	3 W × 2(8 Ω)
Device interface	USB3.0 × 2; HDMI output × 1; 3.5mm audio output interface × 1; TF card slot × 1
Network input (10/100M)	Rj45×1
2.4G WIFI	support
Input power	100-240V
Operating power consumption	≤28W
Standby power consumption	≤0.5W
Operating temperature	0 ~ 40°C
Operating humidity	20% ~ 85%RH, relative humidity, no condensation
Overall dimensions (W×D×H)	305 × 28.8 × 508.4 mm
Wall mounting holes	Horizontal 180 × Vertical 308
Net weight	5.0kg