



Description:

The conference management server is a high-performance server specially used for conference systems. Working with system software, it can realize conference appointment, sign-in, voting, conference room management and other functions.

Feature:

- * High-quality 1.0mm galvanized steel plate, stable structure, double-ball high-speed fan, excellent heat dissipation.
- * 1U rack-mounted design, stable structure and excellent heat dissipation.
- * Support hot swap, support up to 4 hard drives, support RAID0, 1, 5, 10.
- * Dedicated remote port supports remote management.
- * 2 Gigabit Ethernet ports, support port aggregation function.
- * Dedicated server power supply, support redundant power supply.

Specification:

Model	TR-0600T
GPU	Integrated display CPU latest graphics processing core
Processor	E3-v5 quad core processor
RAM	Standard 8G DDR4, support maximum 64G DDR4
BIOS	128Mb SPI Flash EEPROM with AMI BIOS
Onboard LAN	2 10/100/1000M bps network ports support port aggregation
Remote control	1 RTL8201N dedicated remote interface, support intelligent platform management interface; support virtual media and KVM
IDE controller	4xSATAIII (support hot swap)
RAID	Support RAID 0, 1, 5, 10
I/O interface	2xUSB 3.0, 4xUSB2.0 (2 on the front, 2 on the rear), 1xVGA, 1xIPMI independent remote management port, 1xRS232 COM port
Hardware monitoring	Fault/Error/Overload and Alarm (including Disk/RAID/Power/Fan/Temp/IO performance)
Hard disk	2T (3.5 inch) mechanical enterprise hard drive
Box qty	The 4 hard disk extraction boxes are equipped with locking devices, and the sliding rail design makes the hard disk extraction more convenient
Hard drive hot swap	Support hard disk hot swap
Power	250W
Working voltage	AC 100-240V, 50/60Hz
MTBF	50000/H (MTBF)
Working temperature	-10°C~60°C
Relative humidity	5%-90%, no condensation
Dimension	479.4×650×44mm, with guide rails on both sides of the case
Weight	9.62kg