



HD video seamless switching matrix

TV-9108UHM



Description

Specifically designed for the 2K HD market, the 8- channel input and output HD 2K 60 seamless matrix supports 8- channel HDMI video signal input, 8- channel HDMI video signal output, and digital HD 1920×1080P 60Hz signal. The all-in-one design is simple to operate and portable, bringing great convenience to application and maintenance .

Features

- *Equipped with 8- channel HDMI input interface and 8- channel HDMI output interface , the input and output resolution supports 1920×1080P 60Hz ;
- *Integrated matrix, supports hot swap, plug and play;
- *Support seamless video switching , no flash screen, no black screen and other transition states ;
- *Support plan retention and calling;
- *Equipped with power-off on-site switching memory protection function and unique ESD static protection function;
- *It has one RS-232 port, one RS-485 port, and one network port, supporting control via RS - 232, RS - 485, and TCP/IP commands. It also has physical buttons on the front panel and supports infrared OSD remote control.
- *Equipped with EDID management function , you can choose default EDID or on-site learning .

Specification

Digital video input	8× HDMI digital video input interface
Digital video output	8× HDMI digital video output interface
Power switch	1 × switch button
Communication interface	1 × RS-232, 1 × RS-485, 1 × Ethernet port
Upgrade	1 × UPDATE upgrade interface
Panel buttons	8 × input buttons, 8 × output buttons, 6 × function buttons
Indicator light	1 × power indicator light, 1 × signal execution light
Infrared	1 × Infrared sensor receiver
Power supply	12 V 2 A
Dimensions (L × W × H)	482.6×209×44mm
Rated power consumption	18W
Weight	2.6kg
Ambient temperature	-10 °C—+45°C
Ambient humidity	10%-80%