



Content Management Terminal TF-LT06155

Embedded software: information release management software V1.6



Feature

- *Supports customized display of program content through the information release system, supports playback of pictures, videos, audio, files and other material resources, and supports multiple audio and video encoding formats, picture formats, and file formats.
- *The program supports setting playback mode and schedule, such as periodic playback, continuous playback, interstitial playback, idle playback, etc. The validity period of the program can also be set.
- *The device supports timed power on/off tasks, timed restart tasks, and timed screen off tasks, which can be set to single, daily, custom and other modes.
- *The device supports interstitial subtitles (marquee), and supports customizing text content through the information release system, including text size, text background, text color, scrolling speed, and display position.
- *The device supports adjusting playback volume, device restart, device time synchronization, etc.
- *The screen is light-resistant, 4K high-definition display, with high brightness and contrast.
- *The device supports touch interaction and supports vertical screen display of promotional materials.

Specification

Display screen	55-inch LCD touch screen, supports 20-point infrared touch
Resolution	4K
Display ratio	9:16
Display area	680.4×1209.8mm
Brightness	300 cd/m ²
Contrast	≥1200:1 (Typ.)
Total number of colors	16.7M colors
Refresh rate	50/60Hz
Response time	8(Typ.)(GtoG)
Viewing angle	178 degrees horizontal, 178 degrees vertical full viewing angle
Operating system	Android 11.0
Processor	Quad-core 64-bit processor, up to 2.0GHz



Content Management Terminal TF-LT06155

Embedded software: information release management software V1.6

Running memory	4G
Storage memory	32G
Touch recognition	≥1.5mm (opaque objects such as fingers and stylus)
Service life	≥60,000 hours
Anti-light interference	Normal use when strong light changes such as sunlight, incandescent lamps, fluorescent lamps, etc.
Surface hardness	Mohs 7-level explosion-proof tempered glass
Network	Support Ethernet/wireless WiFi, 10M/100M adaptive Ethernet
Interface	USB2.0×1, USB3.0×1, HDMI output×1, RJ45×1, 3.5mm audio×1
Speaker	2×10W
Input power	AC110-240V 50/60Hz
Power consumption of the whole machine	≤110W
Standby power consumption	≤1.5W
Operating temperature	0°C-38°C
Operating humidity	10%-95%
Storage temperature	0°C-40°C
Storage humidity	10%-95%
Dimensions of the whole machine (W×D×H)	731.8×500.4×1900mm
Net weight (bare machine)	57kg
Gross weight (packaging)	58.5kg

Dimensional drawing

