




Professional Speaker

TS-608/ TS-610/ TS-612/ TS-615



Description

It works with the professional amplifiers and audio processors, forming a set of high-end professional sound system with perfect sound effects and outstanding vocal performance. It is applicable to theaters, karaoke rooms, high-end conference rooms, multipurpose halls and other places. It can also work with the subwoofer to compose a high-performance satellite box.

Features

- * Use a mid-woofer unit and a circular polyethylene diaphragm compressed tweeter unit.
- * 15mm plywood housing, light weight, wear-resistant spray paint processing, and dust-proof net cotton outside.
- * The frequency divider in precise design is used to optimize the vocal MF performance.
- * Multiple screw hoisting holes, a pole socket with a diameter of 35mm, various installation methods.



Specification

Model	TS-608/TS-610
Impedance	8Ω
Frequency response(-10dB)	60Hz~20KHz
Rated power	200W
Peak Power	800W
SPL (±2dB) within a specified frequency band	96dB/W/M
Coverage angle	(H)80° (V)60°
Tweeter	1.4" compressed tweeter × 1
Woofer	8" woofer × 1
Dimension (H×W×D)	246×243×442
Weight	9.5kg

Model	TS-612	TS-615
Impedance	8Ω	8Ω
Frequency response	50Hz~20KHz	45Hz~20KHz
Rated power	350W	450W
Peak Power	1400W	1800W
SPL (±2dB) within a specified frequency band	121dB	123dB
THD	0.967% @5.15KHz	
Coverage angle	(H)80° (V)60°	(H)80°(V)60°
Tweeter	1.7" compressed tweeter × 1	1.73" compressed tweeter × 1
Woofer	12" woofer × 1	15"woofer × 1
Dimension (H×W×D)	560×360×380mm	660×435×430mm
Weight	19.2Kg	25.8Kg