PROFESSIONAL SPEAKER

TS Series

TS-608 / TS-610 / TS-612 / TS-615



MODELS IN THE RANGE

TS-608	200 W rated · 800 W peak	8"
TS-610	200 W rated · 800 W peak	10"
TS-612	350 W rated · 1400 W peak	12"
TS-615	450 W rated · 1800 W peak	15"

Description

It works with the professional amplifiers and audio processors, forming a set of high-end professional sound system with perfect sound effects and outstanding vocal performance. It is applicable to theaters, karaoke rooms, high-end conference rooms, multipurpose halls and other places. It can also work with the subwoofer to compose a high-performance satellite box.

Theaters · Karaoke rooms · Conference rooms · Multipurpose halls

Features

- Use a mid-woofer unit and a circular polyethylene diaphragm compressed tweeter unit.
- 15mm plywood housing, light weight, wear-resistant spray paint processing, and dust-proof net cotton outside.
- The frequency divider in precise design is used to optimize the vocal MF performance.
- Multiple screw hoisting holes, a pole socket with a diameter of 35mm, various installation methods.

Specification

MODEL	TS-608 8″ woofer	TS-610 10″ woofer	TS-612 12″ woofer	TS-615 15″ woofer
ELECTRICAL				
Impedance	8 Ω	8 Ω	8 Ω	8 Ω
Rated power	200 W	200 W	350 W	450 W
Peak power	800 W	800 W	1400 W	1800 W
ACOUSTIC				
Frequency response	60 Hz – 20 kHz (–10 dB)	60 Hz – 20 kHz (–10 dB)	50 Hz – 20 kHz	45 Hz – 20 kHz
SPL (±2 dB) within a specified frequency band	96 dB/W/M	96 dB/W/M	121 dB	123 dB
THD	—	—	0.967% @ 5.15 kHz	—
Coverage angle	H 100° × V 60°	H 100° × V 60°	H 80° × V 60°	H 80° × V 60°
DRIVERS				
Tweeter	1.4″ compressed tweeter × 1	1.4″ compressed tweeter × 1	1.7″ compressed tweeter × 1	1.73″ compressed tweeter × 1
Woofer	8″ woofer × 1	10″ woofer × 1	12″ woofer × 1	15″ woofer × 1
PHYSICAL				
Dimension (H × W × D)	246 × 243 × 442 mm	322 × 295 × 512 mm	560 × 360 × 380 mm	660 × 435 × 430 mm
Weight	9.6 kg	15.2 kg	19.2 kg	25.8 kg

Specifications are subject to change without notice.