itc

Description

TS-8202 double screen touch paperless smart desktop with 15.6-inch high-definition front screen design, built in a 10.1 inch screen tablet in rear panel , equipped with integrated lifter, seamless, non-backplane connection, to fulfill smooth high-end out looking. To match with paperless conference terminal, it completely realizes the interactive paperless powerful conference function.

Features

* Touch ultra-thin high-definition display is with aluminum alloy shell, sandblasting anodized surface treatment, ultra-thin LCD screen design, 6.8 mm thickness for the edge of the shell
* Adopt 15.6-inch multi-point capacitive touch high-definition LCD screen, resolution up to 1920 × 1080dpi, with IPS full view LCD screen, to reach clear and bright display effect.
* Built in a 10.1 inch screen tablet in rear panel, resolution up to 1366×768dpi,to display the name of the participants / position /company name / LOGO / banner / logo, etc., can be user-defined editing, support timing refresh.
* Lifter panel is with aviation aluminum, anodized drawing process, ultra-thin design, width only 73mm.
* Touch ultra-thin high-definition display and ultra-thin round shaft lifter is no exposed cabling, no connection backplane, no exposed screws to ensure elegant appearance of the overall touch screen.
* Lifter supports Hand in hand RS232 control, software control, manual control. Control software can be installed in PC, compatible with the common operating system. It can be unified control or also be any group control the lifter move states, such as up, pause, down, and so on.
* Lifter panel is with up, pause, down buttons, multimedia conference terminal switch interface; lifter supports automatic elevation 14 degrees to ensure that the best viewing angle and touch angle display.
* With power protection function, the lifter desktop panel is with USB interface for datea document import and export.

Specifications

Model	TS-8202
Display Size	15.6inch
Tablet	10.1inch
Display Ratio	16:9
Screen Resolution	1920×1080
Tablet Resolution	1280×800
Display perspective	IPS Full View
Touch Screen Type	Capacitive screen, 10 touch
Interface	1×HDMI, 1×USB2.0
Working Environment	Ambient temperature: 5℃~40℃ ; Relative humidity: ≥ 75%
Working Power Consumption	AC~220V/50Hz/30W
Display Size (L×H×D)	480×73×5mm
Display Size (L×H×D)	380×240×6.8mm
Weight	14.08kg
Color	Silver