



Description

Paperless ultra thin 15.6 inch capacitive LCD lifter, adopt aluminum alloy grinding thin shell, the silver fine texture feels fine, the overall appearance show contracted and modern beauty; intelligent 15 degree angle of elevation, more suitable to the ideal visual Angle; fully functional software, simple interface level, smooth operation, is one of best choice for all kinds of high-end meeting places, as well as the important affairs, business, enterprises and institutions, big events venue.

Features

- * Document review: support multi format documents, include common format: doc/docx/xls/xlsx/ppt/pptx/pdf/html/htm and so on.
- * Load USB disk: through the USB, review the documents or upload and share with other attendees.
- * Electronic whiteboard: support single whiteboard or multi attendees share with one board at the same time.
- * Conference communication: support timely communication with one or multi attendees.
- * Handwritten remark: handwriting remark on any pages, save remarks and upload to server, convenient for files after meeting.
- * Screen broadcast: support free screen sharing, any attendee can share his local pages with other attendees by screen broadcasting.
- * Asynchronous browsing: attendees can asynchronous browse, exit the broad cast page and review local documents.
- * Windows mode: Switch the paperless terminals as normal computer usages.
- * Conference service: calling services during meeting, for example: Tea, Pen, Paper and so on, can custom input service requirements
- * Web Browsing: support browse Ethernet network, visit OA, mailbox and so on.
- * Conference record: make notes at any time during meeting, save and upload to server.
- * Sign in management: start the sign-in or unify sign-in control, and view the current status.
- * Topic management: switch freely and enabled for different topics.
- * Voting management: Chairman can start, conclude the voting, review statistical results.
- * Signal management: Chairman can broadcast anyone's local screen image to all attendees, or conclude the sharing image of any attendee.
- * Central control: Chairman can control welcome page, conference information, display name, conference slogan on the terminals during meeting, support lift up/down, on/off uniformly.

Features

- * The LCD panel can be open and unfold automatically, ultra-thin screen design, delicate and beautiful appearance, reveal the fuselage super modern aesthetic feeling.
- * Electric control, with 15 degree angle of elevation, achieves the best effect of perspective, flexible use, high stability, good anti-seismic property.
- * 15.6 inch ultra thin touch LCD monitor, High resolution image digital LCD screen, display effect is clear and bright, can adjust the backlight, to prevent too light or too dark cause fatigue.
- * Low power consumption design, small heat, excellent heat dispersion, support standby dormancy etc. power saving mode.
- * Exquisite surface treatment process, good appearance and hand feeling are both good, mechanical structure design is very stable and reliable, mean free error time is long.
- * Pure network architecture, system wiring is simple, very convenient for debugging maintenance.
- * It can realize the remote control, remote diagnosis, automatic updates and upgrades. It can use single and centralized control.

Specifications

Model	TS-8401A
Screen Size	15.6 inch IPS Retinal HD screen
View Angle	Horizontal viewing angle:0~170, vertical viewing angle:0~170
Screen Ratio	16:9
LCD Resolution	1920×1080P
Touch Technology/Surface rigidity	Capacitive/ 7 level
Touch points/ Induction Strength	10 points/<10g
Touch response Time	5ms
LCD Size	388×245×9mm
Operation System	Windows 10
Processor	INTEL 1037U/dual core /1.8G
Memory	4G DDR3
Hard Disk	SSD 64G
Network Card	Gigabit LAN
Input Interface	1× GigE Vision,1×485 uplink interface, 1×USB
Lifting Touch Mode/Time	Touch-tone or software control/ 10000 times
Lifting Time	21.5S
Lifting Angle	Intelligent 15 degree
Working Environment	Environment temperature 5℃~40℃, Relative humidity ≥75%
Power Consumption	AC~220V/50Hz/40W
Weight	17Kg
Dimension	487×70×700mm